



MINI MULLION READER SMARTPHONES & RFID CARD



Scale 1



COMPATIBILITY

- MIFARE® credentials
- Bluetooth® & NFC smartphones
- SECard software
- OSDP™ / SSCP protocols



LET YOUR IMAGINATION FLOW

Customization of the multicolor LEDs (RGB, 360 colors)



PRINTING OF YOUR LOGO using digital UV or pad printing

«Skin effect» new customization technology



CERTIFICATIONS



EASY TO INSTALL

The Architect® One Blue is a mullion RFID reader specially designed for installation in small spaces, for example on door frames or narrow flushbox mounting, etc.

Its small size and intelligent design make it easy to incorporate into any installation environment with no spacer required (included on metal). The plug-in/plug-out connector cable and the round mounting holes make the installation easier.

STANDING THE TEST OF TIME

The reader's IK10 certified vandal-proof structure has been optimized to resist knocks and malicious acts. It is designed to withstand harsh environments (IP65 level excluding connectivity): dust, heavy rain, frost, etc.

MOBILE ACCESS MULLION READER

The Architect® One Blue is the most compact RFID cards and virtual Bluetooth® reader (Low Energy) or NFC smartphones - designed to be installed on a narrow profile with ease.

WELCOME TO HIGH SECURITY

The reader uses the latest MIFARE® DESFire® EV2 contactless chip technologies with new data security mechanisms:

- **Secure Messaging EV2:** secure transaction method based on AES-128 with protection against interleaving and replay attacks.
- **Proximity Check:** improved protection against relay attacks.

All public encryption algorithms can be used (3DES, AES, RSA, SHA, etc.), which are recommended by official data security agencies (such as the French national agency ANSSI). It uses an EAL5+ crypto processor to improve data protection and privacy.

INSTINCTIVE ACCESS CONTROL

Your smartphone becomes your access key by eliminating the constraints of traditional access control. Choose your favorite identification mode and make your access options both secure and much more instinctive!



Card Mode

Place your smartphone in front of the reader as a standard card.



Remote Mode

Activate remote control mode to remotely check your access points.



Tap Tap Mode

Tap your smartphone twice in your pocket for close or remote access.



Hands-free Mode

Just walk past the reader! There's nothing else to it!



SPECIFICATIONS

Operating frequency/Standards	13.56 MHz: ISO14443A types A & B, ISO18092 Bluetooth®																		
Chip compatibility	MIFARE® Ultralight® & Ultralight® C, MIFARE® Classic & Classic EV1, MIFARE Plus® (S/X) & Plus® EV1, MIFARE® DESFire® 256, EV1 & EV2, CPS3, NFC (HCE), PicoPass® (CSN only), iCLASS™ (CSN only) STid Mobile ID® (NFC & Bluetooth® virtual card), Orange Pack ID																		
Functions	Read only: CSN or private ID (sector/file) / Secure Protocol (Secure Plus) / Secure Read Write																		
Communication interfaces & protocols	TTL protocol Data Clock (ISO2) or Wiegand (ciphered mode S31) / RS485 (ciphered mode S33) with secure communication protocols SSCP & SSCP2 ; OSDP™ V1 (plain communication) & V2 (SCP secure communication)																		
Decoder compatibility	Compatible with EasySecure interface																		
Reading distances**	Up to 6 cm / 2.36" with a MIFARE® DESFire® EV2 or Classic card Up to 20 m / 65.6 ft with a Bluetooth® smartphone (adjustable distances on each reader)																		
Data protection	Yes - Software and physical protection to EAL5+ secure data storage with certified crypto processor																		
Light indicator	2 RGB LEDs - 360 colors Configuration by card (standard or virtual with STid Settings application), software or external command (0V) according to the interface																		
Audio indicator	Internal buzzer with adjustable intensity Configuration by card (standard or virtual with STid Settings application), software or external command (0V) according to the interface																		
Power requirement / Power supply	150 mA/12 VDC Max - 9 VDC to 15 VDC																		
Connections	2 versions: A - 3 m rugged cable outlet / B - 3 m plug-in/plug-out connector cable																		
Material	ABS-PC UL-V0 (black) / ASA-PC-UL-V0 UV (white)																		
Dimensions (h x w x d)	111,5 x 42,2 x 22 mm / 4.33" x 1.65" x 0.87" (general tolerance following ISO NFT 58-000 standard)																		
Operating temperatures	- 30°C to + 70°C / -22°F to + 158°F / Humidity: 0 - 95%																		
Tamper switch	Accelerometer-based tamper detection system with key deletion option (patented solution) and/or message to the controller																		
Protection / Resistance	IP65 Level excluding connector - Weather-resistant with waterproof electronics compliant with CEI NF EN 61086 standard Reinforced vandal-proof structure IK10 certified																		
Mounting	Wall mount, door frame mount or European mullion flush boxes mount (drilling 32 mm x2) Compatible with any surfaces and metal walls without spacer																		
Certifications	CE, FCC & UL																		
Part numbers	<p>X = connector version: A - cable, B - cable with connector y: case color (1: black - 2: white)</p> <table border="0"> <tr> <td>Secure read only - TTL Wiegand / Data Clock</td> <td>ARC1S-R31-X/BT1-xx/y</td> </tr> <tr> <td>Secure read only / Secure Plus - TTL Wiegand / Data Clock</td> <td>ARC1S-S31-X/BT1-xx/y</td> </tr> <tr> <td>Secure read only - RS485</td> <td>ARC1S-R33-X/BT1-7AB/y</td> </tr> <tr> <td>Secure read only / EasySecure - RS485</td> <td>ARC1S-R33-X/BT1-7AA/y</td> </tr> <tr> <td>Secure read only / Secure Plus - RS485</td> <td>ARC1S-S33-X/BT1-7AB/y</td> </tr> <tr> <td>Secure read only / Secure Plus / EasySecure - RS485</td> <td>ARC1S-S33-X/BT1-7AA/y</td> </tr> <tr> <td>Secure read/write SSCP - RS485</td> <td>ARC1S-W33-X/BT1-7AA/y</td> </tr> <tr> <td>Secure read/write SSCP2 - RS485</td> <td>ARC1S-W33-X/BT1-7AD/y</td> </tr> <tr> <td>Secure read/write OSDP™ - RS485</td> <td>ARC1S-W33-X/BT1-7OS/y</td> </tr> </table>	Secure read only - TTL Wiegand / Data Clock	ARC1S-R31-X/BT1-xx/y	Secure read only / Secure Plus - TTL Wiegand / Data Clock	ARC1S-S31-X/BT1-xx/y	Secure read only - RS485	ARC1S-R33-X/BT1-7AB/y	Secure read only / EasySecure - RS485	ARC1S-R33-X/BT1-7AA/y	Secure read only / Secure Plus - RS485	ARC1S-S33-X/BT1-7AB/y	Secure read only / Secure Plus / EasySecure - RS485	ARC1S-S33-X/BT1-7AA/y	Secure read/write SSCP - RS485	ARC1S-W33-X/BT1-7AA/y	Secure read/write SSCP2 - RS485	ARC1S-W33-X/BT1-7AD/y	Secure read/write OSDP™ - RS485	ARC1S-W33-X/BT1-7OS/y
Secure read only - TTL Wiegand / Data Clock	ARC1S-R31-X/BT1-xx/y																		
Secure read only / Secure Plus - TTL Wiegand / Data Clock	ARC1S-S31-X/BT1-xx/y																		
Secure read only - RS485	ARC1S-R33-X/BT1-7AB/y																		
Secure read only / EasySecure - RS485	ARC1S-R33-X/BT1-7AA/y																		
Secure read only / Secure Plus - RS485	ARC1S-S33-X/BT1-7AB/y																		
Secure read only / Secure Plus / EasySecure - RS485	ARC1S-S33-X/BT1-7AA/y																		
Secure read/write SSCP - RS485	ARC1S-W33-X/BT1-7AA/y																		
Secure read/write SSCP2 - RS485	ARC1S-W33-X/BT1-7AD/y																		
Secure read/write OSDP™ - RS485	ARC1S-W33-X/BT1-7OS/y																		

DISCOVER OUR CREDENTIALS...



13.56 MHz or dual frequency
ISO cards & key holders



Bluetooth® & NFC smartphones
using STid Mobile ID® application

*Our readers read only the iCLASS™ UID/Chip Serial Number. They do not read secure HID Global's iCLASS™ cryptographic protections. **Caution: information about the distance of communication: measured from the center of the antenna, depending on the type of identifier, size of the identifier, operating environment of the reader, temperatures, power supply voltage and reading functions (secure reading).

Legal statements: STid, STid Mobile ID® and Architect® are trademarks of STid SAS. All other trademarks are property of their respective owners. This document is the exclusive property of STid. STid reserves the right to stop any product or service for any reason and without any liability - Noncontractual photographs.

...AND OUR ERGONOMIC MANAGEMENT TOOLS



SECARD
SECard configuration kit and SSCP,
SSCP2 & OSDP™ protocols



STid Mobile ID®
Online Portal
Web platform for remote management
of your virtual badges

Headquarters / EMEA

13850 Gréasque, France
Tel.: +33 (0)4 42 12 60 60

PARIS-IDF Office

92290 Châtenay-Malabry, France
Tel.: +33 (0)1 43 50 11 43

STid UK Ltd. LONDON

Hayes UB11 1FW, UK
Tel.: +44 (0) 192 621 7884

STid UK Ltd.

Gallows Hill, Warwick CV34 6UW, UK
Tel.: +44 (0) 192 621 7884

NORTH AMERICA Office

Irving, Texas 75063-2670, USA
Tel.: +1 469 524 3442

LATINO AMERICA Office

Cuahtémoc 06600 CDMX, México
Tel.: +521 (55) 5256 4706

AUSTRALIA / APAC Office

Ultimo, Sydney NSW 2007, Australia
Tel.: +61 (0)2 9274 8853

info@stid.com

www.stid-security.com