

NOX CPA G3 • N267-G3

Control panel with LCD display

Control panel to the NOX System with 128 x 64 pixel LCD graphic display, white background. Integrated alarm buzzer, numerical keypad with “clear = C” and “enter = E” buttons and two scroll keys with variable functions and 4 programmable status LED’s.

NOX CPA G3 specifications

- Graphic control panel in PVC-plastic.
- For surface wall mount.
(Can be recessed for lectern mount with N258 / N308)
- 128 x 64 pixel matrix display, 7 lines with 21 characters each
- Possibility of company logo on the display
- White LED backlight
- Freely programmable internal buzzer
- 4 freely programmable LED status lights
- Supports multiple languages



N258



N308

Technical data

	Unit	Min.	Nominal	Max.
Supply voltage (VBUS)	VDC	8.0	15.0	16.0
Current consumption at 15 VDC	mA	12 ¹		37 ²
Current consumption at 9VDC	mA	16 ³		57 ⁴
Operating temperature	°C	0	25	40
Air humidity at 40 ° C (non condensing)	% RH			93
Dimensions	mm	177 x 115 x 25		
Protection according to IEC 60529:2001		IP20		

1) and 3) = Without backlight, buzzer and LEDs

2) and 4) = With backlight, buzzer and LEDs

Terminal connections

Terminal P2	+	-	A	B
Pin	8-16 VDC	GND	Bus A	Bus B
Description	Supply voltage (VBUS)		Bus connection	

